

NOTE: Additional information requests may be added to this form based on specific industry requirements.

Instructions: Vendor to complete Sections 1 and 2 of this form.

Section 1 – Vendor Information

Company Name: _____

Address: _____

Phone: _____ Fax: _____

Main Contact: _____ Email: _____

RFQ Contact: _____ Email: _____

Quality Contact Name: _____ Email: _____

Quality Contact Phone: _____

Web Site: _____

Other information: _____

Number of employees: _____ Number of years in business: _____

Owner years of experience in this business: _____

See Section 2 on the next page

Section 2 – Vendor Capability and Industry Specific Questionnaire

Manufacturing Certifications		Yes/No	Please complete answers in this column. Please note if these capabilities are “In House” or outsourced
	AS9100		
	J-STD-001		
	IPC-610		
	IPC-7711/21		
	ISO-9001		
	Other	List	
Average Lead Time for CCA			
	High Volume	%	
	Low Volume	%	
First Time PWB Yield		%	
First Time CCA Yield		%	
Laminate Material Capability			
	Laminate Material Used	List with Specs	
	Plated Through Holes		
	SMT		
	Panel Size Configurations		
	Maximum	(X, Y) (mm)	
	Minimum	(X, Y) (mm)	
	Maximum PWB Thickness		
	Single Sided	(in)	
	Double Sided	(in)	
	Multilayer	(in)	
	Rigid Flex	(in)	
	Other	List	
	Laminate Testing Capabilities		
	X-ray		
	TDR		
	Hi-pot		
	AOI		
	Netlist		
	Other	List	
PWA Assembly Capability			
	Plated Through Holes		
	Lead Free Solder		
	Leaded Solder		
	SMT		
	Lead Free Solder		
	Leaded Solder		

Selective Solder System			
	Lead Free Solder		
	Leaded Solder		
Pick and Place System			
	Lead Free Solder		
	Leaded Solder		
Testing Capability			
	X-ray		
	In Circuit Testing		
	Bed of Nails		
	Flying Probe		
	Functional		
	Other		
	Thermal Testing		
	Maximum UUT Size	(L x W x H)	
	Minimum UUT Size	(L x W x H)	
	Maximum Temperature	°C	
	Minimum Temperature	°C	
	Maximum Temperature ROC	°C per minute	
	Dynamic Monitoring		
	Vibration Testing		
	Maximum UUT Size	(L x W x H)	
	Minimum UUT Size	(L x W x H)	
	Maximum Frequency		
	Longitudinal	Hz	
	Latitudinal	Hz	
	Vertical	Hz	
	Maximum Amplitude		
	Longitudinal	g	
	Latitudinal	g	
	Vertical	g	
	Shock Testing		
	Basic Shock		
	Maximum Frequency	ms half sine wave	
	Maximum Amplitude	g	
	Ballistic Shock		
	Maximum Frequency	ms half sine wave	
	Maximum Amplitude	g	
	Gunfire Shock		

	Maximum Frequency	ms half sine wave	
	Maximum Amplitude	g	
	Dynamic Monitoring		
	Other	List	
Conformal Coating			
	Brushed Method		
	Sprayed Method		
	Dipped Method		
	Selective Method		
	Potting		
	Other	List	
Conformal Coating Types			
	Parylene		
	Acrylic Resin (AR)		
	Epoxy (ER)		
	Polyurethane (UR)		
	Silicone (SR)		
Previous subcontractor for government contracts?			
	Dates		
	Braches of service		
	Which prime contractors		